

Optics

- 16 or 22m viewing distance options
 - 16m – 4 x 0.5W LEDs
 - 22m – 6 x 0.5W LEDs
- LEFT, RIGHT, UP and DOWN printed acrylic legend panel to be ordered separately

Body

- Extruded aluminium body housing electronics and LEDs
- Three mounting options:
 - Ceiling
 - Wall
 - Suspended (Supplied with 1m wire suspension kit)
- Input voltage 24V DC
- Supplied complete with driver
- Current consumption:
 - 16m: 0.1A
 - 22m: 0.125A

Note: LED exit sign can only be used as part of a Pathfinder system

Order Codes

LED Exit Sign 16m

4 x 0.5W LED	Ceiling Mounted	PFDCEILING
4 x 0.5W LED	Wall Mounted	PFDWALL
4 x 0.5W LED	Suspended	PFDSUSPENDED

Legends

DOWN LEGEND	SINGLE SIDED	PFDLPSSD
UP LEGEND	SINGLE SIDED	PFDLPSSU
LEFT LEGEND	SINGLE SIDED	PFDLPSSL
RIGHT LEGEND	SINGLE SIDED	PFDLPSSR
DOWN LEGEND	DOUBLE SIDED	PFDLPDSD
UP LEGEND	DOUBLE SIDED	PFDLPDSU
TO SIDE LEGEND	DOUBLE SIDED	PFDLPDST

Note: Legends to be ordered separately

Options

22m version	Add suffix /22M	i.e. PFDCEILING/22M
22m version (LEGENDS)	Add suffix /22M	i.e. PFDLPSSD/22M

Legends



Up



Down



Left



Right




Wall Mount



Ceiling Mount

Dimensions



Version	L	W	H	KG
16m	176	28	134	0.6
22m	256	28	180	0.9

To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER