

pathfinder LED stairwell

LED IP 20

Optics

- 2 x 1W LEDs
- Acrylic diffuser optic
- High output LEDs provide 50,000 hours life expectancy

Body

- Steel and aluminium body housing electronics & LEDs
- Suitable for wall mounting vertically or horizontally
- Input voltage 24V DC
- Supplied complete with driver
- Current Consumption: 0.115A

Note: LED stairwell can only be used as part of a Pathfinder system



Order Codes

LED Stairwell

2 x 1W LED
2 x 1W LED

White
Silver

PFDSTAIRW
PFDSTAIRS

Dimensions



L	W	H	KG
30	50	230	0.5

To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER

pathfinder LED walkway luminaire

LED IP 20

Optics

- Opal or gridded cover available to control light distribution
- 3 x 0.5W LEDs

Body

- Powder coated sheet steel
- Front cover finished white or silver
- Total consumption 0.115A
- Driver included in fitting
- For installation in cavity wall box (included)



Gridded Cover

Order Codes

Safety LED Walkway Luminaire

Opal Cover White
Gridded Cover White

PFDWWOPW
PFDWWGRW


Options

SILVER FINISH

Replace W with S

i.e. PFDWWOPS

Dimensions



L	W	W ₁	H	KG
155	5	75	84	0.5

To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER