



Optics

- Light Output Options:
 - 11,500 lumens (140W*)
- *Total power consumption including driver based on 4300K light engine
- Open area and aisle distribution patterns available
- Supplied with Acrylic (PMMA) lens
- Available in 4300K
- 100,000 hour life expectancy
- IP66 rated as standard

Body

- Low profile cast aluminium body finished light grey
- Operating temperature from -40°C to +65°C
- Mounting brackets for ceiling and wall mounting to be ordered separately
- Supplied with a 3M PVC cable
- Can only be used in a downlight orientation

powerbay cx

Order Codes

Powerbay CX

- 11,500 lumens 4300K – Symmetrical Distribution
- 11,500 lumens 4300K – Elliptical Distribution

Accessories

- Ceiling and wall mounting bracket

Fixed Output


- PCXAH4KC
- PCXAH4KA

PCXWMB




Ceiling and Wall Mounting Bracket


Dimensions



Photometric Performance



Powerbay cx
elliptical distribution
• LOR = 100%



Powerbay cx
symmetrical
distribution
• LOR = 100%

To Specify

IP66 11,500 lumen floodlight. Cast aluminium body finished grey with PMMA acrylic lens and symmetrical or elliptical light distribution pattern – as Whitecroft Lighting POWERBAY CX