

selise maxi

surface mounted circular LED
floodlight for outdoor applications



Optics

- Light output between 9732 - 36009 lumens
- Asymmetric distribution
- 50° peak beam

Body

- IP66, IK08
- Die cast aluminium body with integrated cooling fins
- 4mm thick tempered glass visor resistant to thermal shock and impact
- Adjustable wall mounting bracket included
- Finished in graphite grey or silver
- Fixed output or Dali dimming gear
- 419W gear in remote box mounted on rear of body
- Ambient operating temperature -20 to +40°C (+30° for 419W version)
- Supplied with IP68 connector
- Electrical Class II

Order Codes


Fixed output, Graphite grey

	Code
9732 lumens (101W)	SEMH04KG
12976 lumens (135W)	SEMH14KG
19465 lumens (202W)	SEMH24KG
25954 lumens (270W)	SEMH34KG
36009 lumens (419W)	SEMH44KG

Options

SILVER FINISH	Replace G with S	ie. SEMH14KS
DALI DIMMING	Replace H with Y	ie. SEMY14KG

Dimensions



Version	Ø	H	W	W ₁	KG
101/133/202W	462	477	100	160	13.8
270W	512	524	100	160	14.0
419W	512	524	184	184	17.2

WINDAGE M²: 0.12


LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 70	L ₇₀ (80,000hrs)	MacAdam 3 SDCM

Equivalent Lamp Types

9732 Lumen Output	1 x 150W SON/HQI-T
12976 Lumen Output	1 x 250W HQI-T
19465 Lumen Output	1 x 250W SON-T
25954 Lumen Output	1 x 400W HQI-T
36009 Lumen Output	1 x 400W SON

Photometric Performance



Asymmetric
270W, 25954 lumen,
4000K
• LOR = 100%

To Specify

IP66 LED wall mounted circular floodlight with die cast aluminium body, glass visor and asymmetric distribution. Electronic control gear to operate 4000K LED light engines producing between 9732 - 36009 lumens. Adjustable wall mounting bracket included – as Whitecroft Lighting SELISE MAXI