

sentry

Emergency: Indoor emergency bulkhead

APPLICATION

- Wall or ceiling mounting (recess option)
- Exit routes
- Corridors
- Exit doors
- Canopies
- Walk ways
- Stairwells

SPECIFICATION

- Supplied with 8W T5 lamp
- Low tack self adhesive legends – please specify separately see page 190
- Viewing distance up to 23m when using legend panel
- Polycarbonate TP(a) snap fix diffuser optic is designed to deliver a directional light distribution
- High impact polycarbonate TP(a) body finished White. Surface and semi-recessed (with White semi-recessing bezel) option
- IP20
- 3 hour maintained or non-maintained versions
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Cable entry options on the side and back of body
- Ambient 0 – 25°C
- Designed and manufactured to meet the requirements of BS EN60598.2.22

Options


-  Easytest – integral self test version available see page 181



SPACING DATA TABLE

Ceiling mounting height (metres)	Lighting level (lux)	Escape route (min 0.2 lux) permanently unobstructed	Escape route (min 1.0 lux) normal risk	Anti Panic (min 0.5 lux) open area
CLEAR PRISMATIC				
2.5	1.2	5.0 13.4 7.3 2.8	1.65 6.0 3.55 0.5	3.3 9.7 5.2 1.7
4	0.5	4.7 13.4 7.9 2.7	– 2.7 0.5 –	1.0 9.5 5.5 0.7
6	0.2	2.8 13.2 7.3 1.3	– – – –	– – – –

DIMENSIONS



FEATURES

	SEN/BH/NM/F8	SEN/BH/M/F8
MODE	Non-maintained	Maintained
DURATION	3 hours	
NORMAL LAMP OUTPUT	–	400 lumens
EMERGENCY LAMP OUTPUT	100 lumens	100 lumens
INPUT VOLTAGE	230/240V – 50Hz	
CIRCUIT WATTS	8W	20W
BATTERY TYPE	High temperature Ni-Cd battery	
RECHARGE TIME	24 hours	

ORDER CODES – SENTRY

8W T5 INDOOR EMERGENCY LIGHTING BULKHEAD

LAMP SUPPLIED	EMERGENCY LIGHTING	EMERGENCY UNIT
1 x 8W T5	3 hour non-maintained	SEN/BH/NM/F8
1 x 8W T5	3 hour maintained	SEN/BH/M/F8

EASYTEST OPTIONS Add suffix to order codes above

/ET  Integral self auto-test, i.e. SEN/BH/M/F8/ET

RECESSING KIT Order separately

SEN/RK Recessing bezel finished White

LOW TACK SELF ADHESIVE LEGENDS Order separately

See page 190 to specify

To specify state:

Surface/semi recessed IP20 8W T5, 3 hour self contained maintained/non-maintained indoor emergency bulkhead with snap fix diffuser optic delivering a directional light distribution. High impact polycarbonate body finished White. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting SENTRY