

sirocco central

High output LED post top
lantern for outdoor applications



Optics

- Outputs between 7160 – 14353 lumens (77 – 153W)
- 4000K, Ra80 LED
- Wide symmetric distribution
- Typical mounting height 6-12m
- Zero upward light
- 80,000 hours to 70% light output L70B20

Body

- IP66, IK08 rated protection
- Die cast aluminium housing
- Primed and powder coated for resistance to saline and corrosive environments
- Graphite grey or silver finish
- Post top mounting suitable for 60mm diameter column spigots
- Supplied with IP67 rated connector
- Fixed output LED driver
- Electrical Class II double insulated
- Suitable for ambient temperatures between -30 to 40°C



Order Codes

Graphite Grey

7160 lumen, 77W
10765 lumen, 115W
14353 lumen, 153W

Fixed Output

SCH14KG
SCH24KG
SCH34KG

Options

SILVER FINISH

Replace G with S


ie. SCH14KS

DALI DIMMING ON REQUEST

Accessories

A wide range of columns and attachments is available. See separate data sheets for details.


Dimensions



Ø ₁	Ø ₂	H	H ₁	KG
680	60	270	120	14.0

WINDAGE M²: 0.08

Photometric Performance



LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	80	L ₇₀ (80,000hrs)	MacAdam 3 SDCM

To Specify

High output IP66 LED post top luminaire for outdoor lighting applications. With die cast aluminium housing and 3 light output options. Fixed output LED driver and IP67 connector for ease of installation – as Whitecroft SIROCCO CENTRAL.