

sirocco discus

IP55 amenity lighting
for open spaces



Optics

- Lamp options:
 - 1 x 70/100W HQI-E

Body

- Fits 60mm diameter column spigot
- IP55 protection and vandal resistant
- Black polyester powder coated cast aluminium alloy top cover, canopy and base
- Lens in UV stabilised polycarbonate
- High purity anodised aluminium louvre
- Suitable for an ambient temperature between -25°C to +35°C

Order Codes

Sirocco Discus
HQI-E 1 x 70W
HQI-E 1 x 100W

SID70H
SID100H



Photometric Performance




1 x 70W HQI-E
• LOR = 49.6%

Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 70W HQI-E	7230	20,000hrs
1 x 100W HQI-E	9400	20,000hrs

Dimensions



W	H	KG	Windage
600	470	8.0	0.28m ²

To Specify

IP55 vandal resistant post top amenity luminaire with cast aluminium alloy top cover, canopy and base, finished black. Lens in UV stabilised polycarbonate and louvre in high purity anodised aluminium. Designed for pole heights of 2.5 – 4m. Integral gear with timed ignitor and all fixings in stainless steel – as Whitecroft Lighting SIROCCO DISCUS