

sirocco discus

IP55 amenity lighting for open spaces

> weblink > **DISC**

Optics

- Lamp options:
 - 1 x 70/100W HQI-E

Body


- Fits 60mm diameter column spigot
- IP55 protection and vandal resistant
- Black polyester powder coated cast aluminium alloy top cover, canopy and base
- Lens in UV stabilised polycarbonate
- High purity anodised aluminium louvre
- Suitable for an ambient temperature between -25°C to +35°C

ORDER CODES

Sirocco Discus


HQI-E 1 x 70W	SID70H
HQI-E 1 x 100W	SID100H

DIMENSIONS



W	H	KG	WINDAGE
600	470	8.0	0.28m ²

PHOTOMETRIC PERFORMANCE



- 1 x 70W HQI-E
- LOR = 49.6%

TO SPECIFY

IP55 vandal resistant post top amenity luminaire with cast aluminium alloy top cover, canopy and base, finished black. Lens in UV stabilised polycarbonate and louvre in high purity anodised aluminium. Designed for pole heights of 2.5 – 4m. Integral gear with timed ignitor and all fixings in stainless steel – as Whitecroft Lighting SIROCCO DISCUS



sirocco globe

IP55 amenity lighting for open spaces

> weblink > **GLOB**

Optics

- Lamp options:
 - 1 x 70/150W HQI-E

Body

- Fits 76mm diameter column spigot
- IP55 protection and vandal resistant
- Vandal resistant polycarbonate bowl
- High purity anodised aluminium louvre
- Suitable for an ambient temperature between -25°C to +35°C

ORDER CODES


Sirocco Globe Clear Top

HQI-E 1 x 70W	SIG70HCO
HQI-E 1 x 150W	SIG150HCO

Sirocco Globe Covered Top


HQI-E 1 x 70W	SIG70HCC
HQI-E 1 x 150W	SIG150HCC

DIMENSIONS



W	H	KG	WINDAGE
600	600	11.4	0.23m ²

PHOTOMETRIC PERFORMANCE



- 1 x 70W HQI-E Covered
- LOR = 35.6%

TO SPECIFY

IP55 post top amenity luminaire with 600mm dia vandal resistant polycarbonate bowl. Integral control gear with timed ignitor and louvre. All fixings in stainless steel – as Whitecroft Lighting SIROCCO GLOBE

