

sirocco spoke

IP55 amenity lighting for open spaces

> weblink > **SPOK**

Optics

- Lamp options:
 - 1 x 70/100W HQI-E

Body

- Fits 76mm diameter column spigot
- IP55 protection and vandal resistant
- Black polyester powder coated cast aluminium alloy top cover, canopy and base
- Lens in UV stabilised polycarbonate
- High purity anodised aluminium louvre
- Suitable for an ambient temperature between -25°C to +35°C



ORDER CODES


Sirocco Spoke

HQI-E 1 x 70W	SIS70H
HQI-E 1 x 100W	SIS100H

LAMP PERFORMANCE


Wattage	IL@25°C	Lamp Life
1 x 70W HQI-E	6000	20,000hrs
1 x 100W HQI-E	8200	20,000hrs

DIMENSIONS



Version	W	H	KG	WINDAGE
SIS70H	710	480	16.5	0.40m²
SIS100H	710	480	17.0	0.40m²

PHOTOMETRIC PERFORMANCE



1 x 70W HQI-E
• LOR = 51%

TO SPECIFY

IP55 vandal resistant post top amenity luminaire with cast aluminium alloy top cover hub, spokes, rim and base, finished black. Lens in UV stabilised high impact acrylic and louvre in high purity anodised aluminium. Designed for pole heights of 2.5 – 4m. Integral gear and all fixings in stainless steel – as Whitecroft Lighting SIROCCO SPOKE