

sirocco spoke

IP55 amenity lighting
for open spaces



Optics

- Lamp options:
 - 1 x 70/100W HQI-E

Body

- Fits 76mm diameter column spigot
- IP55 protection and vandal resistant
- Black polyester powder coated cast aluminium alloy top cover, canopy and base
- Lens in UV stabilised polycarbonate
- High purity anodised aluminium louvre
- Suitable for an ambient temperature between -25°C to +35°C




Order Codes

Sirocco Spoke
HQI-E 1 x 70W
HQI-E 1 x 100W


SIS70H
SIS100H

Dimensions



Version	W	H	KG	Windage
SIS70H	710	480	16.5	0.40m ²
SIS100H	710	480	17.0	0.40m ²

Photometric Performance



1 x 70W HQI-E
• LOR = 51%

Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 70W HQI-E	7230	20,000hrs
1 x 100W HQI-E	9400	20,000hrs

To Specify

IP55 vandal resistant post top amenity luminaire with cast aluminium alloy top cover hub, spokes, rim and base, finished black. Lens in UV stabilised high impact acrylic and louvre in high purity anodised aluminium. Designed for pole heights of 2.5 – 4m. Integral gear and all fixings in stainless steel – as Whitecroft Lighting SIROCCO SPOKE