

slot

recessed blade exit sign

> weblink > **SLOT**

Optics

- Max 27m viewing distance
- Lamp options:
 - 1 x 8W T5
- 8mm thick Perspex legend panels, double sided, to be ordered separately
- Maximum projection below the ceiling 175mm

Body

- Fully recessed white high grade polycarbonate recessed body mounted in ceiling tile with winged fixings adjustable from below with white lip trim, recess depth 83mm. Light dispersal cover with slot for legend panel
- 3 hour maintained or non-maintained versions
- High temperature Ni - Cd battery with constant current charger and LED charge indicator
- Ambient 0 – 25°C
- Input voltage 230/240V – 50Hz
- Circuit Watts 8W (20W maintained version)




ORDER CODES


Slot		3 hr Emergency
T5 1 x 8W	3 hour non-maintained	SLOTNMF8
T5 1 x 8W	3 hour maintained	SLOTMF8
Options		
EASYTEST	Add suffix /ET to order code	i.e. SLOTNMF8/ET
LEFT/RIGHT LEGEND	(Double sided)	SLOTLP/RL
DOWN LEGEND	(Double sided)	SLOTLPDD
UP LEGEND	(Double sided)	SLOTLPUD

Note: Available with COMET. Please refer to our sales office for details

LEGENDS



DIMENSIONS



TO SPECIFY

Recessed 8W T5 IP20 blade exit sign in 3 hour self contained maintained or non-maintained versions. Light dispersal cover with slot for 8mm thick Perspex legend panels, projection below the ceiling <176mm, polycarbonate body recess <83mm mounted in ceiling tile with winged fixings. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting SLOT

