



Optics

- Lamp options:
 - 1 x 26W to 32W TC-T multi-watt or 1 x 70W CDM-T (Downlight)
 - 2 x 26W TC-T (Up/downlight)
- Anodised aluminium reflector
- Toughened glass cover

Body

- Wall mounted luminaire with downlight or twin up/downlight versions
- Cast aluminium body finished black or white
- 3 point screw fixing with gasket joint to achieve IP65
- High frequency control gear on fluorescent version
- Magnetic control gear with timed ignitor on CDM-T version



Downlighter



Up/Downlighter

Order Codes


Downlighter	White	Black
TC-T 1 x 26W or 32W	SPWD18H126-32W	SPWD18H126-32B
CDM-T 1 x 70W	SPWD18C70W	SPWD18C70B

Twin Up/Downlighter	White	Black
TC-T 2 x 26W	SPWT18H226W	SPWT18H226B

Lamp Performance


Wattage	IL@25°C	Lamp Life
1 x 26W TC-T	1800	13,000hrs
1 x 32W TC-T	2400	13,000hrs
1 x 70W CDM-T	6600	12,000hrs

Dimensions



Version	D	W	H	KG
Down TC-T	184	284	271	4.0
Down CDM-T	184	284	271	5.2
Up/Down	184	284	490	5.0

Photometric Performance



1 x 70W CDM-T
• LOR = 63%



2 x 26W TC-T
• LOR = 51%

To Specify

IP65 Wall mounted cylindrical down or up/down lighter, with cast aluminium body & toughened glass cover. For TC-T or CDM-T lamps – as Whitecroft Lighting SPECTRE