

spectre 200 wallwasher

Downlighters: Asymmetric compact fluorescent downlighters

APPLICATION

- Retail
- Corridor walls
- Conference room walls
- Reception areas
- Painting and wall hangings
- Signage

SPECIFICATION

- Lamp options:
 - 1 x 18W TC-D
 - 1 x 42W TC-T
 - 2 x 18/26W TC-D
- IP20 protection
- High frequency ballast housed in remote pack
- Specular reflector
- Mounting ring in die cast aluminium
- Thermoplastic ceiling trim, White RAL 9010
- Lamps not supplied




LAMP PERFORMANCE MATRIX

WATTAGE	IL@25°C	LAMP LIFE
1 x 18W TC-D	1200	12,000
1 x 26W TC-D	1800	
1 x 42W TC-T	3200	

PHOTOMETRY

Spectre Wallwasher


1 x 18W TC-D Lamp



LOR = 63%

Spectre Wallwasher


2 x 26W TC-D Lamps



LOR = 45%

Spectre Wallwasher


1 x 42W TC-T Lamp



LOR = 47%

Spectre Wallwasher

2 x 18W TC-D Lamps



LOR = 50%



Spectre 200 Wallwasher showing asymmetric light distribution


ORDER CODES – SPECTRE 200 WALLWASHER

RECESSED CIRCULAR COMPACT WALLWASHER


SUPPLIED LESS LAMP	BEZEL COLOUR	LUMINAIRE
1 x 18W TC-D	White	SPW22-118W
2 x 18W TC-D		SPW22-218W
2 x 26W TC-D		SPW22-226W
1 x 42W TC-T		SPW22-142W

To specify state.
 Recessed compact asymmetric IP20 wallwashing downlight. Die cast aluminium mounting ring and RAL 9010 thermoplastic ceiling trim. Remote high frequency gear box. Overall diameter not to exceed 228mm and recess depth not to exceed 165mm – as Whitecroft Lighting SPECTRE WALLWASHER

DIMENSIONS



ACCESSORIES



IP20 Remote box gear