

spectre ergo

Exterior: IP65 Wall mounted luminaire

APPLICATION

- Feature lighting
- Atriums
- Walkways
- Building façades
- Showrooms
- Feature uplighting (interior applications only)

SPECIFICATION

- Lamps:
 - 26W TC-T
 - 42W TC-T
 - 70W SON-T
 - 70W CDM-T
 - 150W CDM-T
- Die cast aluminium and thermoplastic construction
- Silver anodised aluminum reflector
- Class 1 protection
- Anti glare cylinder
- Integral control gear
- IP65 – dust tight and water jet proof (mounted in downlight position only)
- Lamp replacement without tools
- Supplied less lamp



QuickLink

ERGO

Go




PHOTOMETRY

Spectre Ergo Medium

1 x 26W TC-T Lamp



- SHR MAX = 0.902
- LOR = 34%




Spectre Ergo Large


1 x 70W CDM-T Lamp




- SHR MAX = 0.632
- LOR = 53%



DIMENSIONS



Medium version
26W TC-T



Large version
42W TC-T 70W SON-T
70W & 150W CDM-T

LAMP PERFORMANCE MATRIX

WATTAGE	IL@25°C	LAMP LIFE
26W TC-T	1800	12,000
42W TC-T	3200	12,000
70W SON-T	5600	28,500
70W CDM-T	6600	12,000
150W CDM-T	14000	12,000

WEIGHT AND WINDAGE

VERSION	WATTAGE	WEIGHT	WINDAGE
SPE19	26	4.0Kg	0.06m ²
SPE28	42/70/150	6.6Kg	0.13m ²

ORDER CODES – SPECTRE ERGO

IP65 WALL MOUNTED LUMINAIRE


SUPPLIED LESS LAMP	MEDIUM 190 Ø	LARGE 275 Ø
1 x 26W TC-T	SPE19F26	—
1 x 70W SON-T	—	SPE28S70
1 x 42W TC-T	—	SPE28F42
1 x 70W CDM-T	—	SPE28C70
1 x 150W CDM-T	—	SPE28C15

MOUNTING ACCESSORIES:

For mounting accessories please refer to column and adaptors on page 323

To specify state:

Directionally adjustable wall mounted lantern with cast aluminium gear enclosure. 26/42W TC-T, 70W SON-T, 70/150W CDM-T lamp. Decorative back light component and anti-glare cylinder. IP65 – as Whitecroft Lighting SPECTRE ERGO



Indirect lighting



For suspended options, see Ergo
page 93