

Spectre

Exterior: IP65 Exterior downlighter and up/downlighter

OPTIC


- Lamp options:
 - 1 x 26W to 32W TC-T multi-watt or 1 x 70W CDM-T (Downlight)
 - 2 x 26W TC-T (Up/downlight)
- Anodised aluminium reflector with toughened glass cover
- Supplied Less Lamp

BODY


- Wall mounted luminaire with downlight or twin up/downlight versions
- Cast aluminium body finished black or white
- IP65
- High frequency gear as standard



PHOTOMETRY



1 x 70W CDM-T
• LOR = 63%



2 x 18W TC-T
• LOR = 51%


LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
1 x 26W TC-T	1800	12,000hrs
1 x 32W TC-T	2400	12,000hrs
1 x 70W CDM-T	6600	12,000hrs



Up/Downlighter

DIMENSIONS



Version	W	W ₁	H	KG
Down TC-T	184	284	271	4.0
Down CDM-T	184	284	271	5.2
Up/Down	184	284	490	5.0

ORDER CODES – SPECTRE

SUPPLIED LESS LAMP	WHITE	BLACK
TC-T 1 x 26W or 32W	SPWD18H126-32W	SPWD18H126-32B
CDM-T 1 x 70W	SPWD18C70W	SPWD18C70B
TWIN UP/DOWN	WHITE	BLACK
TC-T 2 x 26W	SPWT18H226W	SPWT18H226B

To specify state:

IP65 Wall mounted cylindrical down/up-down luminaire with cast aluminium construction.
For TC-T or CDM-T lamps – as Whitecroft Lighting SPECTRE

QuickLink

SPEC

Go