

spectre SL

Surface ceiling mounted cylindrical LED luminaire for outdoor applications



Optics

- Light output options:
 - 2000 lumens (23W)
- Wide beam symmetrical distribution
- Zero light pollution
- Clear flat acrylic diffuser in bezel or acrylic feature optic
- Anodised aluminium reflector

Body

- Extruded anodised aluminium
- IP65 IK10 rated protection
- Finished in Anthracite Grey
- Suitable for ambient temperatures between -20°C to +40°C
- Dali dimming as standard

Order Codes

Spectre SL

2000 Lumen (23W) Clear diffuser

SPLAY164K

2000 Lumen (23W) Acrylic feature glass

SPLBY164K

Options

3000K


Replace 4 with **3**

i.e. **SPLAY163K**



Acrylic feature glass

Dimensions



Ø
184


H
329

KG
4.0

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 3 SDCM
3000K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 3 SDCM

Photometric Performance



Clear diffuser
23W 2000 lumen
• LOR = 100%

To Specify

IP65 Surface ceiling mounted cylindrical LED luminaire with extruded aluminium body and clear diffuser or part screened feature optic. With downward distribution having zero upward light – as Whitecroft Lighting SPECTRE SL.