

# spectre SL

## Surface ceiling mounted cylindrical LED luminaire for outdoor applications



### Optics

- Light output options:
  - 1645 lumens (4000K – 24W) - Clear diffuser
  - 1629 lumens (4000K – 24W) - Acrylic feature glass
- Wide beam symmetrical distribution
- Zero light pollution
- Clear flat acrylic diffuser in bezel or acrylic feature optic
- Anodised aluminium reflector

### Body

- Extruded anodised aluminium
- IP65 IK10 rated protection
- Finished in Anthracite Grey
- Suitable for ambient temperatures between -20°C to +40°C

### Order Codes

#### Spectre SL

1645 Lumen (24W) Clear diffuser

**SPLAH164K**

1629 Lumen (24W) Acrylic feature glass

**SPLBH164K**

#### Options

DALI DIMMING


Replace H with Y

i.e. SPLAY164K



Acrylic feature glass

### Dimensions



Ø  
184

H  
329

KG  
4.0

### LED Performance


Colour Temp  
4000K

Ra (CRI)  
≥ 80

Life Expectancy  
L<sub>70</sub> (50,000hrs)

Colour Consistency  
MacAdam 4 SDCM

### Photometric Performance



Clear diffuser  
24W 1645 lumen  
• LOR = 100%

### To Specify

IP65 Surface ceiling mounted cylindrical LED luminaire with extruded aluminium body and clear diffuser or part screened feature optic. With downward distribution having zero upward light – as Whitecroft Lighting SPECTRE SL.