

spectre SL

Surface ceiling mounted cylindrical LED luminaire for outdoor applications



Optics

- Light output options:
 - 1645 lumens (24W) - Clear diffuser
 - 1629 lumens (24W) - Acrylic feature glass
- Wide beam symmetrical distribution
- Zero light pollution
- Clear flat acrylic diffuser in bezel or acrylic feature optic
- Anodised aluminium reflector

Body

- Extruded anodised aluminium
- IP65 IK10 rated protection
- Finished in Anthracite Grey
- Suitable for ambient temperatures between -20°C to +40°C

Order Codes

Spectre SL

1645 Lumen (24W) Clear diffuser

SPLAH164K

1629 Lumen (24W) Acrylic feature glass

SPLBH164K

Options

DALI DIMMING
3000K


Replace H with **Y**
Replace 4 with **3**

i.e. **SPLAY164K**
i.e. **SPLAH163K**



Acrylic feature glass

Dimensions



Ø
184

H
329

KG
4.0

LED Performance


Colour Temp
4000K

Ra (CRI)
≥ 80

Life Expectancy
L₇₀ (50,000hrs)

Colour Consistency
MacAdam 4 SDCM

Photometric Performance



Clear diffuser
24W 1645 lumen
• LOR = 100%

To Specify

IP65 Surface ceiling mounted cylindrical LED luminaire with extruded aluminium body and clear diffuser or part screened feature optic. With downward distribution having zero upward light – as Whitecroft Lighting SPECTRE SL.