

Spectre Wall

IP65 wall mounted luminaire for outdoor applications



IK08

IP65



Optics

- Direct/indirect distribution
- 4000K and 3000K LED options
- Internal anodised aluminium reflector
- 4mm thick clear toughened glass visor

Body

- IP65, IK08 protection rated
- Die cast aluminium body
- Finished in silver/grey RAL 9007
- Primed and coated for resistance to corrosive and saline environments
- For outdoor applications within 3km of the coast, an enhanced paint finish can be offered on request
- Fixed output as standard, DALI optional
- Requires dedicated wall mounting bracket, to be ordered separately

Order codes

Direct/Indirect

4000K LED	Fixed Output	LL/CW	L70
2663 lumen, 45.6W LED	SWTLH24K	58	50k

Accessories

Essential wall bracket	SWBKT
------------------------	-------


Options

DALI dimming	Change 'H' to 'Y'	ie. SWTLY24K
3000K	Change 4K to 3K	i.e. SWTLH23K
This product uses 1 DALI driver		

LED Performance

Colour Temp	RA (CRI)	Colour consistency
4000K	>90	MacAdam 3 SDCM


Dimensions



L	W	H	KG	FC (W)	FC (H)
280	185	350	6.9	72	210

Cable entry 95mm below centre of mounting bracket to hole centre, suitable for 9-12mm diameter cable

Photometric Performance



Direct/Indirect
LED 2663 Lumens
LOR = 100.0%

To Specify

Spectre Wall mounted IP65 direct only or direct/indirect luminaire. Die cast aluminium body with toughened glass visor. Primed and coated for resistance to corrosion and saline environments. Requires wall mounting bracket, supplied separately - as Whitecroft SPECTRE WALL
