

spectre wx

Wall mounted conical LED luminaire for outdoor applications



Optics

- Light output options:
 - 1119 lumens (4000K - 17.9W)
- Forward throw downward distribution
- 4mm thick, thermal shock resistant, tempered clear flat glass

Body

- Die cast aluminium
- Coated for corrosion and saline environment resistance
- IP65 IK07 rated protection
- 1st fix wall mounting backplate
- Finished in Graphite Grey or Silver
- Suitable for ambient temperatures between -20°C to +40°C (-5°C to +25°C for emergency versions)
- Choice of integrated emergency options:
 - 3 hour self contained
 - 3 hour COMECS addressable



Order Codes

Spectre WX
1119 lumen (17.9W)

Standard
SPXAH14KG

3 hr Emergency
SPXAH14KGEM


Options

SILVER
COMECS

Replace G with **S**
Add suffix **/EP**

i.e. **SPXAH14KS**
i.e. **SPXAH14KG/EP**

Dimensions




L	W	H	KG
224	375	329	4.0

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L ₇₀ (60,000hrs)	MacAdam 4 SDCM

Photometric Performance



17.9W 1119 lumen
• LOR = 100%

To Specify

IP65 Wall mounted conical LED luminaire with die cast aluminium body. With forward throw downward distribution having – as Whitecroft Lighting SPECTRE WX.