

# speedpack trunking

**Industrial:** Rapid fit continuous trunking system



## APPLICATION

A pre-wired trunking system with a selection of attachments and accessories to suit a variety of applications where a rapid installation process is valued, for example:

- Retail
- Warehousing
- Education
- Factories

## SPECIFICATION


- Rigid steel trunking section with 5 core 2.5mm<sup>2</sup> LSF cabling and pre-positioned power sockets
- Supplied in lengths of up to 4.5m with simple push-in couplers for continuous runs
- Clip-on suspension brackets fitted every 2m along trunking length
- Gear tray with high frequency control gear and optional emergency pack
- Gear tray includes fixed plug with simple 3 position circuit selection
- Gear tray retained with turn buckle fixings
- Supplied without lamps which should be ordered separately
- A rear guide allows for additional electrical cables to be run along the trunking
- Reflectors can be fitted to luminaire sections via gear tray turnbuckles
- Luminaires can be mounted continuously or spaced at a standard luminaire distance with blank infill panels

## T5 TRUNKING SECTIONS




| LAMPWAY / DESCRIPTION                                           | ORDER CODE      | LENGTH | WEIGHT (KG) |
|-----------------------------------------------------------------|-----------------|--------|-------------|
| 1 x 28/54W ST with 5 x 2.5mm <sup>2</sup> cable & 1 x socket    | <b>SPTT1285</b> | 1239   | 2.2         |
| 2 x 28/54W ST with 5 x 2.5mm <sup>2</sup> cable & 2 x socket    | <b>SPTT2285</b> | 2478   | 4.3         |
| 3 x 28/54W ST with 5 x 2.5mm <sup>2</sup> cable & 3 x socket    | <b>SPTT3285</b> | 3717   | 6.3         |
| 1 x 35/49/80W ST with 5 x 2.5mm <sup>2</sup> cable & 1 x socket | <b>SPTT1355</b> | 1539   | 2.7         |
| 2 x 35/49/80W ST with 5 x 2.5mm <sup>2</sup> cable & 2 x socket | <b>SPTT2355</b> | 3078   | 5.3         |
| 3 x 35/49/80W ST with 5 x 2.5mm <sup>2</sup> cable & 3 x socket | <b>SPTT3355</b> | 4617   | 7.5         |



## DIMENSIONS




## LUMINAIRE INSERTS





| GEAR TRAY  | STANDARD       | EMERGENCY          | LENGTH | WEIGHT (KG) |
|------------|----------------|--------------------|--------|-------------|
| 1 x 28W T5 | <b>SPTH128</b> | <b>SPTH128EMIN</b> | 1239   | 1.2         |
| 1 x 35W T5 | <b>SPTH135</b> | <b>SPTH135EMIN</b> | 1539   | 1.3         |
| 1 x 49W T5 | <b>SPTH149</b> | <b>SPTH149EMIN</b> | 1539   | 1.3         |
| 1 x 54W T5 | <b>SPTH154</b> | <b>SPTH154EMIN</b> | 1239   | 1.3         |
| 1 x 80W T5 | <b>SPTH180</b> | <b>SPTH180EMIN</b> | 1539   | 1.3         |
| 2 x 28W T5 | <b>SPTH228</b> | <b>SPTH228EMIN</b> | 1239   | 1.2         |
| 2 x 35W T5 | <b>SPTH235</b> | <b>SPTH235EMIN</b> | 1539   | 1.3         |
| 2 x 49W T5 | <b>SPTH249</b> | <b>SPTH249EMIN</b> | 1539   | 1.3         |
| 2 x 54W T5 | <b>SPTH254</b> | <b>SPTH254EMIN</b> | 1239   | 1.3         |
| 2 x 80W T5 | <b>SPTH280</b> | <b>SPTH280EMIN</b> | 1539   | 1.3         |





## ATTACHMENTS





| T5 WHITE REFLECTOR SINGLE AND TWIN | ORDER CODE    | LENGTH | WEIGHT (KG) |
|------------------------------------|---------------|--------|-------------|
| 28/54W                             | <b>SPTR28</b> | 1239   | 1.5         |
| 35/49/80W                          | <b>SPTR35</b> | 1539   | 1.9         |




| T5 LOUVRED REFLECTOR SINGLE | ORDER CODE     | LENGTH | WEIGHT (KG) |
|-----------------------------|----------------|--------|-------------|
| 28/54W                      | <b>SPTRL28</b> | 1239   | 2.1         |
| 35/49/80W                   | <b>SPTRL35</b> | 1539   | 2.7         |



| T5 MIRROR REFLECTOR SINGLE AND TWIN | ORDER CODE     | LENGTH | WEIGHT (KG) |
|-------------------------------------|----------------|--------|-------------|
| 28/54W                              | <b>SPTRP28</b> | 1239   | 1.9         |
| 35/49/80W                           | <b>SPTRP35</b> | 1539   | 2.5         |



| T5 NARROW BEAM REFLECTOR SINGLE | ORDER CODE     | LENGTH | WEIGHT (KG) |
|---------------------------------|----------------|--------|-------------|
| 28/54W                          | <b>SPTRN28</b> | 1259   | 0.5         |
| 35/49/80W                       | <b>SPTRN35</b> | 1559   | 0.5         |



# speedpack trunking



**Industrial:** Rapid fit continuous trunking system

## ATTACHMENTS




| 3 CIRCUIT TRACK ADAPTER | ORDER CODE     | L    | L1  | L2  | L3  | WEIGHT (KG) |
|-------------------------|----------------|------|-----|-----|-----|-------------|
| For 28/54W trunking     | <b>SPTM328</b> | 1240 | 500 | 325 | 415 | 2.1         |
| For 35/49/80W trunking  | <b>SPTM335</b> | 1540 | 800 | 325 | 415 | 2.6         |

## DIMENSIONS




## CORNER JUNCTIONS




### 90 DEGREE 2 WAY CORNER JUNCTIONS

|                |                                          |
|----------------|------------------------------------------|
| <b>SPTKPS2</b> | 2 way fixed corner junction              |
| <b>SPTKPA</b>  | individual corner extension (2 required) |



### 90 DEGREE 3 WAY CORNER JUNCTIONS




|                |                                          |
|----------------|------------------------------------------|
| <b>SPTKPS3</b> | 3 way fixed corner junction              |
| <b>SPTKPA</b>  | individual corner extension (3 required) |




### VARIABLE 2 WAY CORNER JUNCTIONS

|                |                                          |
|----------------|------------------------------------------|
| <b>SPTKPV2</b> | 2 way variable corner junction           |
| <b>SPTKPA</b>  | individual corner extension (2 required) |

## DIMENSIONS




## ACCESSORIES



### EYELET TRUNKING SUSPENSION

#### SPTSAD EYE


A clip on stainless steel trunking suspension point with an eyelet for chain link suspension



### TRUNKING ENDCAP

#### SPTED


An IP20 trunking end-cap with two integral knock-outs for supply or through wiring



### WIRE TRUNKING SUSPENSION

#### SPTSAS

A clip on stainless steel trunking suspension point with clutch adjustable wire suspension kit for up to 1.5m drops (ceiling fixture included)



### TRUNKING CONNECTOR

#### SPTSV


A galvanised steel connector with claw spring retention for fast, tool free connection of trunking sections



### T-BAR SUSPENSION

#### SPTSTB


A clip on stainless steel trunking suspension point with a 'T'-bar hanger clip for 15mm Tee ceilings



### LUMINAIRE ATTACHMENT BRACKET

#### SPTLBK

A trunking bracket for attaching non standard luminaires to the trunking



### BLIND COVER

|                   | L    | W  | AP.KG |
|-------------------|------|----|-------|
| <b>SPTSTN36-B</b> | 1239 | 60 | 0.8   |
| <b>SPTSTN58-B</b> | 1539 | 60 | 1.0   |

|                   | L    | W  | AP.KG |
|-------------------|------|----|-------|
| <b>SPTSTN36-B</b> | 1239 | 60 | 0.8   |
| <b>SPTSTN58-B</b> | 1539 | 60 | 1.0   |


Steel blind cover plate (IP20) finished White. Cover plates are locked off by two 90 degree rotation quick locks



Glide – see page 83



ACF Duralite – see page 275



### PLASTIC BLIND COVER

|                 | L    | W  |
|-----------------|------|----|
| <b>SPTBA581</b> | 1539 | 60 |

|                 | L    | W  |
|-----------------|------|----|
| <b>SPTBA581</b> | 1539 | 60 |

Plastic blind cover plate for installation without tools by steel spring clips.

These covers are only supplied in 1539mm lengths but can be easily cut down on site

#### To specify state:

Flourescent continuous trunking system with rigid section body and multiple attachments. Twist locking luminaires and attachments for quick and easy tool free installation – as Whitecroft Lighting SPEEDPACK TRUNKING