

starline flex IP67

flexible linear IP67 LED tape



Optics

- Low output version 390-400 lumens / 5W per metre
- Medium output version 780-1000 lumens / 10W per metre
- Wattage excludes driver losses
- 60,000 hours life to L80B10
- 2900K and 4300K options

Body

- IP67 rated protection when encapsulated
- IP40 without encapsulation
- Flexible linear strip
- Supplied with self-adhesive backing tape for ease of installation
- 34mm wide mounting clips recommended spacing every 250mm
- Can be cut to required length on site at 125mm intervals
- Connectors and end caps specified separately
- End connector (to driver) with fitted 2m lead and free ends
- Drivers ordered separately to suit reel length, fixed output or Dali dimming
- 1 encapsulation kit per 13 connectors
- 1 encapsulation tool per project



Connector



Encapsulation kit



Encapsulation tool

Order Codes

Starline flex

Low output, 5W, 400 lm/m, 4300K, 7.5m reel

Low output, 5W, 390 lm/m, 2900K, 7.5m reel

Medium output, 10W, 1000 lm/m, 4300K, 5m reel

Medium output, 10W, 780 lm/m, 2900K, 5m reel

Fixed output

SF67W14K

SF67W13K

SF67W24K

SF67W23K

Driver

IP20 fixed output 25W

CNSLD25

IP20 fixed output 75W

CNSLD75

IP20 fixed output 180W

CNSLD180

IP20 Dali dimming 75W

CSFDY75

IP20 Dali dimming 150W

CSFDY150

Accessories

CONNECTOR FROM REEL TO DRIVER
WITH 2M LEAD AND END CAPS (PACK OF 5)

SF67CON1

FLEX MOUNTING CLIPS (PACK OF 50)

SF67CLIP


ENCAPSULATION KIT

SF67ENCAPKIT

ENCAPSULATION TOOL


SF67ENCAPT00L

Photometric Performance



Medium Output
10W per metre
1000 Lumens
4300K

Dimensions



Version	L	W	H
Low output	7500	12.5	3.5
Medium output	5000	12.5	3.5

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
2900K	≥ 85	L ₈₀ (60,000hrs)	MacAdam 3 SDCM
4300K	≥ 85	L ₈₀ (60,000hrs)	MacAdam 3 SDCM

Number of LED tape reels per driver

Driver type	Code	Low output 7.5m reel (37.5W)	Medium output 5m reel (50W)
Fixed output 25W	CNSLD25	1 (max 5m)	1 (max 2.5m)
Fixed output 75W	CNSLD75	2	1
Fixed output 180W	CNSLD180	4	3
Dali dimming 75W	CSFDY75	2	1
Dali dimming 150W	CSFDY150	4	3

Note: For multiple reels, drivers should be wired in parallel, not in series

To Specify

Flexible linear LED tape IP67 rated with encapsulation. Suitable for cutting to length on site at 125mm intervals. Low or medium output, 2900K or 4300K LEDs – as Whitecroft Lighting STARLINE FLEX IP67