

strato

track mounted directional spotlight

> weblink > **STRA**

Optics

- Lamp options:
 - 35/70W CDM-T

Body

- For use with 3 circuit track
- Electronic control gear
- Ballast housing, shade and trim ring of die cast aluminium painted silver, white or black
- Protective glass integrated in the trim ring
- Swivels 360° and tilts 0-90°. Can also be tilted 90° upwards on the Y-axis
- Specular anodised aluminium reflector. Available with spot (14°), medium (24°) or wide (42°) distribution



ORDER CODES

Spot Reflector (14°)	Colour	
35W CDM-T	Silver	STRA-C35E-M3-11
70W CDM-T	Silver	STRA-C70E-M3-11
Medium Reflector (24°)	Colour	
35W CDM-T	Silver	STRA-C35E-M3-12
70W CDM-T	Silver	STRA-C70E-M3-12
Flood Reflector (42°)	Colour	
35W CDM-T	Silver	STRA-C35E-M3-13
70W CDM-T	Silver	STRA-C70E-M3-13

Options


WHITE	Replace 1st Number 1 with 2 in order code	i.e. STRA-C35E-M3- 21
BLACK	Replace 1st Number 1 with 3 in order code	i.e. STRA-C35E-M3- 31

PHOTOMETRIC PERFORMANCE

70W CDM-T			70W CDM-T			70W CDM-T		
LUX			LUX			LUX		
MH	70W	Ø	MH	70W	Ø	MH	70W	Ø
1.0m	43283	0.3	1.0m	21498	0.4	1.0m	7600	0.8
2.0m	10821	0.5	2.0m	5374	0.8	2.0m	1902	1.5
3.0m	4809	0.8	3.0m	2389	1.3	3.0m	846	2.3
4.0m	2705	1.0	4.0m	1344	1.7	4.0m	476	3.1
Spot 14°			Medium 24°			Flood 42°		



DIMENSIONS



TO SPECIFY

3 circuit track mounted spotlight for 35W or 70W CDM-T lamp with integral electronic gear. Die cast aluminium body, with specular aluminium reflector giving spot (14°), medium (24°) or wide (42°) distribution and with 360° swivel and 0-90° tilt – as Whitecroft Lighting STRATO

