



Optics

- Lamp options:
  - 35/70W CDM-T

Body

- For use with 3 circuit track
- Electronic control gear
- Ballast housing, shade and trim ring of die cast aluminium painted silver, white or black
- Protective glass integrated in the trim ring
- Swivels 360° and tilts 0-90°. Can also be tilted 90° upwards on the Y-axis
- Specular anodised aluminium reflector. Available with spot (14°), medium (24°) or wide (42°) distribution



Order Codes

| Spot Reflector (14°) | Colour |                 |
|----------------------|--------|-----------------|
| 35W CDM-T            | Silver | STRA-C35E-M3-11 |
| 70W CDM-T            | Silver | STRA-C70E-M3-11 |


| Medium Reflector (24°) | Colour |                 |
|------------------------|--------|-----------------|
| 35W CDM-T              | Silver | STRA-C35E-M3-12 |
| 70W CDM-T              | Silver | STRA-C70E-M3-12 |

| Flood Reflector (42°) | Colour |                 |
|-----------------------|--------|-----------------|
| 35W CDM-T             | Silver | STRA-C35E-M3-13 |
| 70W CDM-T             | Silver | STRA-C70E-M3-13 |

Options

|       |                             |                      |
|-------|-----------------------------|----------------------|
| WHITE | Replace 1st Number 1 with 2 | i.e. STRA-C35E-M3-21 |
| BLACK | Replace 1st Number 1 with 3 | i.e. STRA-C35E-M3-31 |

Dimensions



Photometric Performance

| 70W CDM-T |       |     | 70W CDM-T  |       |     | 70W CDM-T |      |     |
|-----------|-------|-----|------------|-------|-----|-----------|------|-----|
| LUX       |       |     | LUX        |       |     | LUX       |      |     |
| MH        | 70W   | Ø   | MH         | 70W   | Ø   | MH        | 70W  | Ø   |
| 1.0m      | 43283 | 0.3 | 1.0m       | 21498 | 0.4 | 1.0m      | 7600 | 0.8 |
| 2.0m      | 10821 | 0.5 | 2.0m       | 5374  | 0.8 | 2.0m      | 1902 | 1.5 |
| 3.0m      | 4809  | 0.8 | 3.0m       | 2389  | 1.3 | 3.0m      | 846  | 2.3 |
| 4.0m      | 2705  | 1.0 | 4.0m       | 1344  | 1.7 | 4.0m      | 476  | 3.1 |
| Spot 14°  |       |     | Medium 24° |       |     | Flood 42° |      |     |

To Specify

3 circuit track mounted spotlight for 35W or 70W CDM-T lamp with integral electronic gear. Die cast aluminium body, with specular aluminium reflector giving spot (14°), medium (24°) or wide (42°) distribution and with 360° swivel and 0-90° tilt – as Whitecroft Lighting STRATO