




Whitecroft Lighting Ltd
Burlington Street
Ashton-under-Lyne
Lancashire OL7 0AX
United Kingdom

Telephone: +44 (0)870 5 087 087
Facsimile: +44 (0)870 5 084 210
email@whitecroftlight.com
www.whitecroftlighting.com

Moorlite · Hitech · Simplex

Torque
Surface or Track mounted spotlight

Spotlights: Surface or Track mounted spotlight

Torque

MOTIVATION

Designed specifically for retail and architectural environments where the quality of light and aesthetics are of key importance. The spotlight version of Torque capitalises on the latest advances in CDM lamp technology. A compact housing and integral gear assembly offers a powerful but aesthetically pleasing solution.

APPLICATION

Retail

- Accent and display lighting
- Feature lighting
- Shop windows
- Merchandising
- Signage

Commercial

- Feature areas
- Receptions
- Atriums
- Foyers
- Museums and galleries

SPECIFICATION

- Lamp options:
 - 35W CDM-TC G8.3 base
 - 70W CDM-T G12 base
- Body: Precision die cast aluminium
- Finish: Silver, White or Black
- Integral electronic gear
- Rotation: 355°
- Tilt: 180°
- Integrated aiming scale
- Mounting - surface and track:
 - Concord®
 - Lytespan® 1
 - Eurotrack
- Reflectors:
 - 11° narrow
 - 20° medium
 - 40° wide
- Toughened glass lamp protector
- 75% LOR
- IP20 protection
- F-mark compliance
- Supplied with lamp



35W CDM-TC
Integral electronic gear




70W CDM-T
Integral electronic gear



Torque CDM Spotlight

Medium

Angle 20°




HGT	LUX		Ø
	35W	70W	
1.0m	21681	43362	0.28m
2.0m	5240	10840	0.56m
3.0m	2409	4818	0.84m
4.0m	1355	2710	1.12m

Torque CDM Spotlight

Flood

Angle 40°




HGT	LUX		Ø
	35W	70W	
1.0m	6454	12908	0.54m
2.0m	1614	3227	1.07m
3.0m	717	1434	1.61m
4.0m	403	806	2.14m


WEIGHT & DIMENSIONS

VERSION	LAMP	WEIGHT FITTING KG
TNS-TC35E	35W CDM-TC	1.3
TNS-C70E	70W CDM-T	1.3


TNS-TC35E
35W CDM-TC
Integral electronic gear




TNS-C70E
70W CDM-T
Integral electronic gear



MAINS TRACK



3 CIRCUIT M3



LYTESPAN® LS1

Eurotrack - 3 Circuit	✓	-
Concord® Lytespan® 1	-	✓
Concord® Lytespan® 1 LP	-	✓

TRACK ADAPTOR SPECIFICATION

Mechanical Load kg	5	3.5
Electric Load	6A	6A

Torque Spotlight

ORDER CODES

SURFACE OR TRACK MOUNTED SPOTLIGHT

11° REFLECTOR	20° REFLECTOR	40° REFLECTOR	COLOUR
TNS-TC35E-#-11	TNS-TC35E-#-12	TNS-TC35E-#-13	Silver
TNS-TC35E-#-21	TNS-TC35E-#-22	TNS-TC35E-#-23	White
TNS-TC35E-#-31	TNS-TC35E-#-32	TNS-TC35E-#-33	Black
TNS-C70E-#-11	TNS-C70E-#-12	TNS-C70E-#-13	Silver
TNS-C70E-#-21	TNS-C70E-#-22	TNS-C70E-#-23	White
TNS-C70E-#-31	TNS-C70E-#-32	TNS-C70E-#-33	Black

MOUNTING OPTIONS Replace # in code above with one of the suffixes below – see pages 172-173 in the main catalogue for track information

LS1	Concord Lytespan e.g. TNS-TC35E-LS1-11
M3	3 Circuit e.g. TNS-TC35E-M3-11
SM	Surface mounted e.g. TNS-TC35E-SM-11

To specify state.
Surface/track mounted mains voltage spotlight with 35W CDM-TC or 70W CDM-T lamp and integral gear. Die cast aluminium construction with aiming scale and fin feature. Narrow 11°/medium 20°/wide 40° reflector. 355 rotation and 180 tilt, gearbox and head to protrude <200mm from the ceiling line as Whitecroft Lighting TORQUE.