

torque spotlight

Display: Surface or track mounted spotlight





APPLICATION

Retail

- Accent and display lighting
- Feature lighting
- Shop windows
- Merchandising
- Signage

Commercial

- Feature areas
- Receptions
- Atriums
- Foyers
- Museums and galleries

SPECIFICATION

- Lamp options:
 - 35W CDM-T G12 base
 - 70W CDM-T G12 base
 - 70W LV-TH
- Body: Precision die cast aluminium
- Finish: Silver or White
- Integral electronic gear
- Rotation: 355°
- Tilt: 180°
- Integrated aiming scale
- Toughened glass lamp protector
- Mounting - surface and track:
 - Concord® Lytespan® 1
 - Direct 3 Eurotrack
- Reflectors:
 - 11° narrow
 - 20° medium
 - 40° wide
- IP20 protection
- F-mark compliance
- Supplied with lamp – 3000K



Surface mounted 35W CDM-T
integral electronic gear

Track mounted 70W CDM-T
integral electronic gear

torque spotlight

Display: Surface or track mounted spotlight

PHOTOMETRY

Torque CDM-T Spotlight Medium

Angle 20°



HGT	35W	LUX	70W	Ø
1.0m	21681	43362	0.28m	
2.0m	5240	10840	0.56m	
3.0m	2409	4818	0.84m	
4.0m	1355	2710	1.12m	

Torque CDM-T Spotlight Flood

Angle 40°




HGT	35W	LUX	70W	Ø
1.0m	6454	12908	0.54m	
2.0m	1614	3227	1.07m	
3.0m	717	1434	1.61m	
4.0m	403	806	2.14m	


WEIGHT AND DIMENSIONS

VERSION	LAMP	WEIGHT FITTING KG
TNS-C35E	35W CDM-T	1.3
TNS-C70E	70W CDM-T	1.3
TNS-T75	75W LV-TH	1.3


TNS-C35E/TNS-T75
35W CDM-T/75W LV capsule
Integral electronic gear



TNS-C70E
70W CDM-T
Integral electronic gear



MAINS TRACK



TRACK ADAPTOR SPECIFICATION	DIRECT 3 – M3	LYTESPAN® – LS1
Mechanical Load kg	5	3.5
Electric Load	6A	6A

LAMP PERFORMANCE MATRIX

WATTAGE	IL@25°C	LAMP LIFE
1 x 35W CDM-T	3300	12,000
1 x 70W CDM-T	6600	12,000
1 x 70W LV-TH	1600	2,000

ORDER CODES – TORQUE SPOTLIGHT

SURFACE OR TRACK MOUNTED SPOTLIGHT

SUPPLIED WITH LAMP

11° REFLECTOR	20° REFLECTOR	40° REFLECTOR	COLOUR
TNS-C35E-#-11	TNS-C35E-#-12	TNS-C35E-#-13	Silver
TNS-C35E-#-21	TNS-C35E-#-22	TNS-C35E-#-23	White
TNS-C70E-#-11	TNS-C70E-#-12	TNS-C70E-#-13	Silver
TNS-C70E-#-21	TNS-C70E-#-22	TNS-C70E-#-23	White
TNS-T75-#-11	TNS-T75-#-12	TNS-T75-#-13	Silver
TNS-T75-#-21	TNS-T75-#-22	TNS-T75-#-23	White

MOUNTING OPTIONS Replace # in code above with one of the suffixes below

LS1	Concord Lytespan, i.e. TNS-C35E- LS1 -11
M3	Direct 3, i.e. TNS-C35E- M3 -11
SM	Surface mounted, i.e. TNS-C35E- SM -11

Note: See pages 57 in the main catalogue for track information

To specify state.

Surface/track mounted mains voltage spotlight with 35W CDM-T or 70W CDM-T lamp and integral gear. Die cast aluminium construction with aiming scale and fin feature. Narrow 11° – medium 20° – wide 40° reflector. 355° rotation and 180° tilt, gearbox and head to protrude <200mm from the ceiling line – as Whitecroft Lighting TORQUE

QuickLink

TNS

Go

torque wallwasher

Display: Surface or track mounted spotlight and wallwasher

APPLICATION

Retail

- Retail
- Vertical shelving
- Vertical displays
- Signage
- Wall texture

Commercial


- Museums and galleries
- Pictures
- Wall hangings
- Signage
- Vertical features
- Wall texture

SPECIFICATION

- Lamp options:
 - 26W TC-T
 - 42W TC-T
- Body:
 - Precision die cast aluminium
 - Silver or White
- Gear:
 - Integral to body
- Rotation 355°
- Tilt 180°
- Integrated aiming scale
- Mounting:
 - Surface track
 - Direct 3 – Eurotrack
 - Concord® Lytespan® 1
 - Surface mounting
- IP20 protection
- F-mark compliance
- Supplied with lamp – 3000K



TNW-T
26W & 42W TC-T



ORDER CODES – TORQUE WALLWASHER

SURFACE OR TRACK MOUNTED WALLWASHER

LAMP SUPPLIED	COLOUR	BASE	ASYMMETRIC REFLECTOR
26W TC-T	Silver	GX24q1	TNW-T26-#-1
	White		TNW-T26-#-2
42W TC-T	Silver	GX24q1	TNW-T42-#-1
	White		TNW-T42-#-2

MOUNTING OPTIONS Replace # in code above with one of the suffixes below

LS1	Concord® Lytespan® 1, i.e. TNS-C15- LS1 -11
M3	Direct 3, i.e. TNS-C15- M3 -11
SM	Surface mounted, i.e. TNS-C15- SM -11

Note: See pages 57in the main catalogue for track information

To specify state:

Surface/track mounted mains voltage compact fluorescent TC-T wallwasher with integral gear. Die cast aluminium construction with aiming scale. 355° rotation and 180° tilt, to protrude <228mm from the ceiling line – as Whitecroft Lighting TORQUE WALLWASHER

WEIGHT AND DIMENSIONS

VERSION	LAMP	TOTAL WEIGHT KG	DIMENSION A
TNW-T26-	26W TC-T	1.3	180
TNW-T42-	42W TC-T	1.4	200

QuickLink

TNW

Go