

torque wallwasher

Display: Surface or track mounted spotlight and wallwasher

APPLICATION

Retail

- Retail
- Vertical shelving
- Vertical displays
- Signage
- Wall texture

Commercial


- Museums and galleries
- Pictures
- Wall hangings
- Signage
- Vertical features
- Wall texture

SPECIFICATION

- Lamp options:
 - 26W TC-T
 - 42W TC-T
- Body:
 - Precision die cast aluminium
 - Silver or White
- Gear:
 - Integral to body
- Rotation 355°
- Tilt 180°
- Integrated aiming scale
- Mounting:
 - Surface track
 - Direct 3 – Eurotrack
 - Concord® Lytespan® 1
 - Surface mounting
- IP20 protection
- F-mark compliance
- Supplied with lamp – 3000K



TNW-T
26W & 42W TC-T



ORDER CODES – TORQUE WALLWASHER

SURFACE OR TRACK MOUNTED WALLWASHER

LAMP SUPPLIED	COLOUR	BASE	ASYMMETRIC REFLECTOR
26W TC-T	Silver	GX24q1	TNW-T26-#-1
	White		TNW-T26-#-2
42W TC-T	Silver	GX24q1	TNW-T42-#-1
	White		TNW-T42-#-2

MOUNTING OPTIONS Replace # in code above with one of the suffixes below

LS1	Concord® Lytespan® 1, i.e. TNS-C15- LS1 -11
M3	Direct 3, i.e. TNS-C15- M3 -11
SM	Surface mounted, i.e. TNS-C15- SM -11

Note: See pages 57in the main catalogue for track information

To specify state:

Surface/track mounted mains voltage compact fluorescent TC-T wallwasher with integral gear. Die cast aluminium construction with aiming scale. 355° rotation and 180° tilt, to protrude <228mm from the ceiling line – as Whitecroft Lighting TORQUE WALLWASHER

WEIGHT AND DIMENSIONS

VERSION	LAMP	TOTAL WEIGHT KG	DIMENSION A
TNW-T26-	26W TC-T	1.3	180
TNW-T42-	42W TC-T	1.4	200

QuickLink

TNW

Go