

vespere wall

architectural
fluorescent wall light



Optics

- Lamp options:
 - 2 x 36W TC-L

Body

- Fabricated steel back plate
- White polyester powder paint
- Curved panel fabricated perforated steel front fascia

Order Codes


Vespere Wall Mounted TC-L 2 x 36W	HF Gear VWMH236	3 hr Emergency VWMH236EMIN
--------------------------------------	--------------------	-------------------------------

Options

DALI DIMMING	Replace H with Y	i.e. VWMY236
SWITCH DIMMING	Replace H with X	i.e. VWMX236
EASYTEST	Add suffix /ET	i.e. VWMH236/ET
COMEPS	Add suffix /EP	i.e. VWMH236/EP
COMET	Add suffix /CT	i.e. VWMH236/CT



Photometric Performance



- 2 x 36W TC-L
- LOR = 40.8%
- SHR MAX = 1.21


Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 36W TC-L	2900	20,000hrs

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.18 0.29 0.32

Dimensions



W	L	H	KG	KG
98	260	430	6.0	7.0

To Specify

Wall mounted compact fluorescent luminaire with curved perforated front panel protruding a maximum of 98mm – as Whitecroft Lighting VESPERE WALL

