

vivant® 600 x 600 mist

> weblink > **VIVM**

ORDER CODES

Vivant 600 x 600 Mist	HF Gear	3 hr Emergency
T5 4 x 14W	VIVMP414	VIVMP414EMIN

Options

DALI DIMMING	Add Y after VIVMP	i.e. VIVMP Y 414
DSI DIMMING	Add D after VIVMP	i.e. VIVMP D 414
SWITCH DIMMING	Add X after VIVMP	i.e. VIVMP X 414
EASYTEST	Add suffix /ET to order code	i.e. VIVMP414/ ET
COMET	Add suffix /CT to order code	i.e. VIVMP414/ CT




LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
1 x 14W T5	1200	24,000hrs

PERFORMANCE GUIDE

Lamps	Illuminance	Spacing
4 x 14W T5	465 lux	2.4m x 2.4m



Maintenance:
0.8
Reflectance:
70/50/20
Ceiling Height:
2.7m
Working Plane:
0.8m

CEILING INTEGRATION

Refer to common ceiling compatibility matrix – See page 310


Exposed T Grids

T25 Lay in
T15 Tegular

Alugrids


SAS AL 15/16
SAS AL 15/08

DIMENSIONS



Version	L	W	H	L ₁	W ₁	KG	KG
Exposed T	584	584	113	571	567	7.5	8.5

PHOTOMETRIC PERFORMANCE



4 x 14W T5
• LOR = 61.7%
• SHR MAX = 1.65

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.41	0.59	0.63

TO SPECIFY

Architectural semi-recessed 600 x 600, T5 luminaire with laterally ribbed opal polycarbonate TP(a) diffuser, curved to match luminance profiler radius and projecting only 28mm below the ceiling. Delivering light spill on the ceiling and a smoothly graduated wall wash – as Whitecroft Lighting VIVANT MIST