

weatherproof

Emergency: IP65 Outdoor emergency bulkhead



APPLICATION

- Exit doors – exterior
- Car parks
- Walk ways
- Leisure centres
- Schools
- Underground walkways

SPECIFICATION

- Supplied with 8W T5 lamp
- Polycarbonate TP(a) screw fixed opal or clear prismatic diffuser with gasket to body
- Low tack self adhesive legends – please specify separately see page 190
- Viewing distance up to 23m when using legend panel
- High grade TP(a) polymer flame and UV resistant body finished White. Surface and semi-recessed (with White semi-recessing bezel) option
- IP65 ingress protection
- 3 hour self contained maintained or non-maintained versions
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Cable entries on the side and back of the body
- Ambient 0 - 25°C
- Designed and manufactured to meet the requirements of BS EN60598.2.22, V8 Kite-marked and ICEL1001

Options

-  Easytest – integral self test version available see page 181

SPACING DATA TABLE

Ceiling mounting height (metres)	Lighting level (lux)	Escape route (min 0.2 lux) permanently unobstructed	Escape route (min 1.0 lux) normal risk	Anti Panic (min 0.5 lux) open area
CLEAR PRISMATIC				
2.5	1.8	4.1 12.7 7.1 2.8	1.4 4.5 4.2 1.3	2.6 7.2 6.1 2.3
4	0.7	3.5 10.5 8.4 3.3	– 2.9 3.0 –	1.9 7.2 6.2 1.6
6	0.3	2.7 10.0 9.5 2.7	– – – –	– – – –
OPAL				
2.5	2.7	4.7 11.9 9.7 3.9	2.2 6.4 5.6 1.9	3.2 8.5 7.3 2.8
4	1.1	5.0 13.4 11.4 4.4	0.7 5.9 5.2 0.4	3.0 9.1 7.8 2.6
6	0.5	4.8 14.1 12.3 4.2	– – – –	– – – –

ORDER CODES – WEATHERPROOF

INDOOR EMERGENCY LIGHTING BULKHEAD

LAMP SUPPLIED	EMERGENCY LIGHTING	OPAL DIFFUSER	CLEAR PRISMATIC DIFFUSER
1 x 8W T5	3 hour non maintained	WBU/NM/3/1128	WBC/NM/3/1128
1 x 8W T5	3 hour maintained	WBU/MA/3/1128	WBC/MA/3/1128

EASYTEST OPTION Add suffix to order codes above

/ET  Integral self auto-test, i.e. WBU/NM/3/1128/ET

RECESSING KIT Order separately

WBU/SRK Recessing bezel finished White

LOW TACK SELF ADHESIVE LEGENDS Order separately

See page 190 to specify

To specify state:

Surface/semi recessed IP65 8W T5, 3 hour self-contained maintained/non-maintained outdoor emergency bulkhead with screw retained opal/clear prismatic diffuser. High grade polymer body finished White. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting WEATHERPROOF

FEATURES

	WBU/NM/3/1128	WBU/MA/3/1128
MODE	Non-maintained	Maintained
DURATION	3 hours	
INPUT VOLTAGE	230/240V – 50Hz.	
CIRCUIT WATTS	8W	20W
BATTERY TYPE	High temperature Ni-Cd battery	
RECHARGE TIME	24 hours	

DIMENSIONS



Recessing kit

QuickLink

WBU

Go