

# Command Professional Area Controllers



Feature packed LonWorks™ area controller



## Features

- Soft button display panel
- Password protected command buttons
- Power, network and network traffic status indication
- Loadshed, system diagnostics, emergency test (2 zone), fire alarm and master on, off, dim buttons
- Time controlled scheduling
- Simple integration and wiring
- Fully distributed intelligence
- Volt free inputs
- Laptop connection point

# Specification

- Mains input
  - Requires 15Vdc remote power supply
- Inputs
  - 3 x volt free inputs
  - Cage clamp terminals cable cross sections from 0.5 to 2.5mm<sup>2</sup>
- Network
  - LonWorks™ network TP/FT-10 (Capacitor decoupled)
  - LonWorks™ Interoperable solution
  - Cable cross sections from 0.5 to 2.5mm<sup>2</sup>
- Network Input
  - LonWorks™ interface - backbone
  - LonWorks™ interface - zone
- Conformity & Standards
  - Generic emission: EN 50081-1
  - Generic immunity: EN 50082-1
  - RFI: EN 55014
  - LonMark™ compliant
- Operating Temperature
  - 0°C to +40°C
- Operating Humidity
  - 10% to 90% non condensing
- Safety
  - EN60950
  - Isolation: 4kV between mains and sensors
- Installation
  - At accesible height but not higher than 1.5 metres
  - Supplied in steel enclosure
- Up to 63 Area controllers can be linked on a project to give control of larger buildings typical landlord and tenant splits (may require a PC Head End)
- 2 versions available:
  - Without TCIP interface
  - With TCIP interface for large networks

---

## Order codes

Command Area Controller	COMPFLACRL
Command Area Controller with TCIP Interface	COMPFTLACRL

## Dimensions

VERSION	L	W	H
Enclosure	355	260	80

## To Specify

Feature packed lighting control system area controller with soft button display panel, 3 volt free inputs, time scheduler and Lonworks™ compatible - as Whitecroft Lighting COMMAND PROFESSIONAL AREA CONTROLLER.

---