

Command Professional Switch Input Unit



Compact DALI addressable switch interface unit



Features

- Complements Command Professional addressable lighting control modules and hubs
- For use with either retractive or latching light switches
- 2 versions available:
 - COMPFSIU - DALI switch interface for mounting behind 2 x single PTM or latching switches or 1 Centre point biased switch (to controls lighting as a Raise lower on and off)
 - COMPFSIU4 - DALI switch interface for mounting behind 4 x single PTM or latching switches or 2 Centre point biased switch (to controls lighting as a Raise lower on and off)
- Fits a 35mm deep switch backbox *

Specification

- Power Consumption
 - 4mA nominal consumption at 15V DALI bus voltage
- DALI Connections
 - Grey -DA and DA
- Connections
 - Black - Common
 - Green - On/Up switch 1
 - Blue - Off/Down switch 1
- Operating Temperature
 - 0°C to +56°C
- Operating Humidity
 - 10% - 90% non-condensing
- Conformity & Standards
 - EMC immunity EN 50082-1
 - EMC emissions EN 50081-1
 - DALI & NEMA compliant
 - IEC Standard 62386-102
 - Supports DALI 2 & 3 byte protocol
- Installation
 - Requires minimum 35mm deep backbox *
 - Switch line requires screened cable
 - Switch line to be kept to a minimum possible distance and below 2 metres
 - DALI is a non isolated bus, switches used with this device must therefore be mains rated

* Supplied by others

Order codes

Switch Input Unit	COMPFSIU
4 channel Switch Input Unit	COMPFSIU4

Dimensions

VERSION	L	H	W
COMPFSIU	54mm	37mm	15mm

To Specify

Compact DALI addressable switch interface unit for use with either retractive or latching light switches. Compatible with the range of Command Professional addressable lighting controls modules and hubs - as Whitecroft Lighting COMMAND PROFESSIONAL COMPFSIU.