

# Concert EX65

Surface mounted IP65 emergency bulkhead



Concert EX65 & Legend

## Optics

- Power consumption;
  - 3.2W maintained
  - 1.2W non maintained
- Clear polycarbonate TP(a) fresnal lens with linear prisms
- Wide light distribution
- 16 long life LEDs
- 151 lumen output
- Self adhesive legend kit available for adhesion to to bulkhead (supplied separately)
- Legends supplied in accordance with BS 5266-1 (ISO7010)
- Legends have a viewing distance of up to 25m

## Body

- IP65/IK10 rated
- High impact polycarbonate TP(a) body finished white
- Surface mounted
- 3 hour maintained as standard (may be wired as non maintained)
- Available with integrated Organic Response for Emergency test and reporting functionality when connected to the Organic Resposne Portal
- Also available with "EW" Routefinder Wireless for addressable emergency testing without the need for a 2 core communication cable
- Supplied with Lithium Iron Phosphate (LiFePO4) battery technology; featuring extended design life reducing replacement frequency to lower total cost of ownership, and advancing sustainability through support for end of life recycling
- Hinged gear tray for easy maintenance
- Cable entry options along the sides and back of the body
- Suitable for operation in low temperature environments

---

## Order codes

### Concert EX65

Concert	3hr Emergency	COMEPS*	Routefinder Wireless	Organic Response
IP65 LED Emergency bulkhead	EX65M3LEM	EX65M3LEP	EX65M3LEW	EXRP65M3LEP

\* COMEPS will work as self test if DALI pair not connected

### Accessories

Self Adhesive Legend Kit	EX65LK/7010
--------------------------	-------------

## Dimensions

L	W	H	KG(EM)
350	120	90	1.2

---

## To Specify

Surface IP65 Emergency LED bulkhead complete with polycarbonate TP(a) fresnal lens. 3hr maintained or non maintained - as Whitecroft Lighting CONCERT EX65.