

Florin Track

High performance, track mounted emergency luminaire



Florin Track | White

Overview

Florin Track emergency luminaire integrates seamlessly into the track system, providing reliable safety lighting exactly where it's needed while maintaining a clean, coordinated aesthetic. Available in black or white and equipped with DALI-2 control gear, it fits effortlessly into modern, connected lighting schemes.

By mounting emergency lighting directly to the track, layouts can evolve as spaces change. Luminaires can be repositioned, added, or adapted without complex rewiring, ensuring the emergency lighting strategy remains as flexible and future-ready as the space it protects.


Lighting Performance

- Open area, escape route and emphasis distribution patterns
- Polycarbonate Tp(a) rated optics
- Light sources available
 - Colour rendition: Ra80
 - Colour temperature: 5000K
- Control gear: DALI-2 as standard
- For specific product variant information, including lifetime, efficacy, power, output and electrical data, please click on the individual part number under 'Order Codes' and view the datasheet

Construction

- Extruded aluminium body with aesthetics to match Lyne Prism and Lyne Fusion
- Available in white and black
- To be surface mounted to Lyne Track
- Supplied with Lithium Iron Phosphate (LiFePO4) battery technology; featuring extended design life reducing replacement frequency to lower total cost of ownership, and advancing sustainability through support for end of life recycling
- LiFePO4 battery life in excess of 6 years if operated within temperature limits

Dimensions



VERSION	L	W	H	KG
All	292mm	87mm	36mm	0.8

To Specify

Track mounted white or black high performance LED emergency luminaire, complete with charge indicator, driver, charger and battery capable of operation in non-maintained mode. Driver to ensure constant light output independent of battery voltage for 3-hours from mains failure – as Whitecroft Lighting FLORIN TRACK